

## MTBP - 18 (Kit)

MTBP – TELESCOPIC Platform




### Telescopic Platform

- Working height 18 Meters
- Side reach up-to 12 Meters
- 200 kg Bucket Capacity
- Kit designed for 7000 kg GVW chassis

## STANDARD FEATURES

- ✓ Telescopic boom (3 elements: main boom + 2 telescopic extension)
- ✓ 360 degrees rotation
- ✓ Max. outreach 12 meters (200 kg)
- ✓ Electronic controls in the basket
- ✓ Engine Start/Stop from control panel
- ✓ Hydraulic controls from the ground, installed on turntable
- ✓ Overload alarm
- ✓ System to automatically limit the outreach depending on the weight in the basket (M+ system)
- ✓ Ground Egress
- ✓ Ideal for street light maintenance work
- ✓ Standard glass filled nylon base with Poly Liner able to withstand 50 kV for 1 min
- ✓ Basket size (L x W x H) 1220 x 610 x 1067 mm
- ✓ Safety Valves against any damage in hydraulic lines
- ✓ Actuated Warning Light System when boom is operational
- ✓ Safety at maximum load and lateral outreach
- ✓ 60° right + 60° left hydraulic rotating basket
- ✓ Automatic basket leveling
- ✓ Emergency manual pump
- ✓ Internally installed electrical and hydraulic hoses



### AVAILABLE OPTIONS

- 12V or 24V electric system
- Working light in the basket
- 230V AC electric socket in the basket

### Contact

#### MERAJ Türkiye


KOSBAŞ Serbest Bölgesi - Sepetlipınar SB Mah.  
107 Cad. Modüler İşyeri No. 5 iç Kapı No.  
Başiskele - Kocaeli 41090 - Türkiye

Tel: +90-262-341-4372  
Ph: +90-543-414-52-70  
E-mail: sales@meraj.com.tr

[www.meraj.com.tr](http://www.meraj.com.tr)

*Text and photos are non-binding. The photos may show extra options only available at extra charge. The right to change make changes in accordance with technical progress is retained.*

## WORKING ENVELOPE



## PERFORMANCE

	Working height	18,00 m		Total length of vehicle	6,44 m***
	Lifting height	16,50 m		Perm. sitting inclination	5°**
	Outreach	12,00 m*		Perm. total weight ≥	6.000 kg
	Size of working cage	1,22 x 0,61 m		Range of rotation	360°
	Working cage load	200 kg*		Wheelbase Carrier chassis	3,60 m***

\* depending on load, angle of rotation and outfit

\*\* with restriction of performance data

\*\*\* Depending on the chassis model

Special Application Trucks & Pumps | Since 1976