

## MTBP - 20 (Kit)

MTBP – TELESCOPIC Platform




### Telescopic Platform

- Working height 20 Meters
- Side reach up-to 14.3 Meters
- 200 kg Bucket Capacity
- Kit designed for 5500 kg GVW chassis











## STANDARD FEATURES

- ✓ Telescopic boom (4 elements: main boom + 3 telescopic extension)
- ✓ Continuous rotation 360 degrees
- ✓ Max. outreach 14.3 meters (200 kg)
- ✓ Electronic controls in the basket
- ✓ Engine Start/Stop from control panel
- ✓ Hydraulic controls from the ground, installed on turntable
- ✓ Overload alarm
- ✓ System to automatically limit the outreach depending on the weight in the basket (M+ system)
- ✓ Ground Egress
- ✓ Ideal for street light maintenance work
- ✓ Aluminum basket or standard glass filled nylon base
- ✓ Safety Valves against any damage in hydraulic lines
- ✓ Actuated Warning Light System when boom is operational
- ✓ Safety at maximum load and lateral outreach
- ✓ 60° right + 60° left hydraulic rotating basket
- ✓ Automatic basket leveling by hydraulic parallelogram
- ✓ Emergency manual pump
- ✓ Internally installed electrical and hydraulic hoses

## WORKING ENVELOPE



## PERFORMANCE

	Working height	20,00 m		Total length of vehicle	6,44 m
	Lifting height	18,00 m		Perm. siting inclination	5°**
	Outreach	14,30 m*		Perm. total weight ≥	5.500 kg
	Size of working cage	1,40 x 0,70 m		Range of rotation	450°
	Working cage load	200 kg		Wheelbase Carrier chassis	3,60 m

\* depending on load, angle of rotation and outfit  
 \*\* with restriction of performance data

### Contact


#### MERAJ Türkiye

KOSBAŞ Serbest Bölgesi - Sepetlipınar SB Mah.  
 107 Cad. Modüler İşyeri No. 5 iç Kapı No.  
 Başiskele - Kocaeli 41090 - Türkiye

Tel: +90-262-341-4372  
 Ph: +90-543-414-52-70  
 E-mail: sales@meraj.com.tr

[www.meraj.com.tr](http://www.meraj.com.tr)

*Text and photos are non-binding. The photos may show extra optionals only available at extra charge. The right to change make changes in accordance with technical progress is retained.*



### AVAILABLE OPTIONS

- 12V or 24V electric system
- Working light in the basket
- 230V AC electric socket in the basket

Special Application Trucks & Pumps | Since 1976